

## Outdoor - Luminaire lifetime

Product Series	Version	L80B10 @ Ta=25°C	L80F10 @ Ta=25°C	L80B20 @ Ta=25°C	L80F20 @ Ta=25°C
<b>LEDway Series</b>	350 mA	>200000	>200000	>200000	>200000
	525 mA	>200000	>200000	>200000	>200000
	700 mA	>105000	>105000	>110000	>105000
<b>304 Series</b>	350 mA	>200000	>200000	>200000	>200000
	525 mA	>200000	>200000	>200000	>200000
	700 mA	>110000	>110000	>110000	>110000
<b>CPY Series</b>	72 LED 350mA	>82000	>81000	>82000	>81000
	138 LED 325mA	>70000	>70000	>70000	>70000
<b>Edge HO Series</b>	120LED 700 mA	>110000	>110000	>110000	>110000
	120LED 1000 mA	>105000	>105000	>105000	>105000
	240LED 700 mA	>110000	>105000	>110000	>110000
	240LED 1000 mA	>100000	>100000	>105000	>100000
<b>RKT Series</b>	Vers. C - Input F - 45W	>200000	>200000	>200000	>200000
<b>XSP R Series</b>	Vers. B - Input A - 54W	>90000	>90000	>90000	>90000
	Vers. B - Input B - 41W	>150000	>145000	>150000	>150000
<b>XSP 1 Series</b>	Vers. B - Input A - 52W	>200000	>200000	>200000	>200000
	Vers. C - Input H - 67W	>200000	>200000	>200000	>200000
	Vers. C - Input E - 98W	>140000	>140000	>140000	>140000
<b>XSP 2 Series</b>	Vers. B - Input B - 101W	>200000	>200000	>200000	>200000
	Vers. C - Input I - 116W	>200000	>200000	>200000	>200000
	Vers. C - Input F - 136W	>170000	>170000	>165000	>165000
<b>XSP R HO Series</b>	Vers. C - Input A - 54W	>90000	>90000	>90000	>90000
	Vers. C - Input B - 41W	>150000	>145000	>150000	>150000
<b>XSP 1 HO Series</b>	Vers. D - Input H - 67W	>200000	>200000	>200000	>200000
	Vers. D - Input E - 98W	>140000	>140000	>140000	>140000
<b>XSP 2 HO Series</b>	Vers. C - Input I - 116W	>200000	>200000	>200000	>200000
	Vers. C - Input F - 138W	>170000	>170000	>165000	>165000
<b>URBAN Series</b>	Vers. A - Input A - 45W	>200000	>200000	>200000	>200000

### NOTES

- LxBy and LxFy accordingly to IEC 62717:2014 (LED modules for general lighting – Performance requirements).
- Values are extrapolated using IESNA TM-21-11 (Projecting Long Term Lumen Maintenance of LED Light Sources).